

Remote Digital & Alarm Indicator

Features

- ✓ **Bright 1" Red LED digital concentration display**
- ✓ **Built-in Alarm and Fault status LED's**
- ✓ **User selectable dual level alarm set points**
- ✓ **Built-in Audio horn alerts personnel to low or high oxygen conditions**
- ✓ **Two tone horn distinguishes between alarm 1 and alarm 2**
- ✓ **Displays Oxygen monitor overall status**



Part # 99091



The Remote Digital Alarm Indicator provides continuous information on the status of the PureAire Oxygen Deficiency Monitor by remotely mirroring the monitor's display and alarm panel. A large, bright red LED display continuously illuminates the O₂ reading from the oxygen monitor up to 250 feet away.

You can select two individual alarm set points to activate the visual alarm LED's and audible horn. High intensity LED's illuminate whenever preset alarm levels are exceeded. It also has an additional fault LED to indicate when system errors occur.

The Remote Digital Alarm Indicator has a 90dB built-in horn to alert personnel when an unsafe condition exists. Housed in a polycarbonate wall mount general purpose enclosure with dimensions of 4.6" (W) x 3.5"(H) x 2"(D) inches.

It easily connects to PureAire' Oxygen monitor using a 3-wire, 18 gauge shielded cable. When connected, the red concentration LED's continuously illuminate to insure proper connection. Remote Digital Alarm Indicators can also be connected to a programmable Logic Controller, PLC, to provide simultaneous alarm and status indications in multiple locations throughout your facility. They can be located up to 250 feet from the risk area to alert employees of an unsafe condition before they enter.

It comes with a full two year parts and labor warranty and will provide continuous remote indication of your Oxygen monitors status for years of unattended operation.

For more information contact PureAire Monitoring Systems, Inc.
557 Capital Drive, Lake Zurich, Illinois 60047 PH: 888-788-8050

E-mail info@pureaire.net Web www.pureaire.net